

# GEKA® plus automatic hose reel EA15SK

available  
now

## GEKA® plus automatic hose reel EA15SK

- Advantages / benefits: ..... Robust, durable and rust-free **stainless steel** construction with **double-sided suspension** of the reel  
**Automatic roll-up of the hose locks** 2x per rotation  
With individually positionable hose stopper for different hose sizes (1/2", 5/8", 3/4")  
Gentle hose guide prevents the hose from jumping off the reel during reeling  
**Suitable for wall, floor and ceiling mounting**  
Hose guide on the axle adjustable in three 45° steps  
**With 12,5 m GEKA® plus water hose WS500 3/4"**, Wall thickness 3,1 mm,  
Operating pressure 11 bar, Made in Germany + **2 m supply hose**
- Material: ..... Housing: made of robust, durable and rustproof stainless steel 1.4301, hose guide rollers, inlet pipe, locking mechanism (toothed washer, catch, spring, snap ring),  
GEKA® plus rotary fitting: stainless steel, hose stopper: black rubber
- Operating pressure at +20 °C: ..... 11 bar
- Temperature range: ..... +4°C to +60°C (hose-dependent)
- Dimensions L x W x H cm: ..... 52 (incl. mount) x 45 x 23,5
- Special note: ..... The automatic hose reel is laid out for 15 m 3/4" hoses with 25 mm or 25 m 1/2" hoses with an outer diameter of 17 mm  
Screws and wall plugs for wall mounting are not included in the scope of delivery  
**Stainless steel swivelling wall mount 165° incl. connecting screws (42.9097.9)**

Connection	Male thread
Male thread mm	26,44
<b>Male thread</b>	<b>G3/4</b>
Capacity of 1/2" hose approx. m	25
Capacity of 5/8" hose approx. m	24
Capacity of 3/4" hose approx. m	15
Hose length approx. m	12,5
Weight approx. kg	18
PU units	1
<b>Article No.</b>	<b>42.9041.9</b>



Robust stainless steel construction



GEKA® plus rotary fitting with full 3/4" water flow



Gradual adjustment



Automatic roll-up of the hose



Locking mechanism can be controlled by pulling at the end of the hose



Gentle hose guide

