

# GEKA® plus quick couplings P *plastic*

Extra  
lightweight


The  
Original

Advantage / benefit:	<b>high resistance to wear, abrasion and resistance to breaking</b>
	Made in Germany
Material:	plastic PA 6 GF 25
Claw distance:	uniform 40 mm, multiple combinations possible compatible with all other GEKA® and GEKA® plus versions
Operating pressure:	<b>max. 15 bar</b>
Vacuum resistance:	up to 10 m water column (WS)
Temperature range:	approx. -5 °C to +100 °C (depending on the seal ring quality)
Seal:	as standard with <b>GEKA® plus shaped seal 300C, patented</b> , temperature range of approx. -10 °C to +90 °C
Colour:	grey
Options:	on request GEKA® plus shaped seal 300V, patented, as well as dirt filters, available for self-assembly
Area of application:	<b>water, suction and pressure hoses</b> , in industry, construction and agriculture, horticulture and domestic water installations

## GEKA® plus hose pieces P

Grommet with striking and hose protecting ribbed profile guarantees fixed hose fit


Hose ID mm	10	13	16	19	25	32
<b>Hose size</b>	<b>3/8"</b>	<b>1/2"</b>	<b>5/8"</b>	<b>3/4"</b>	<b>1"</b>	<b>1 1/4"</b>
Nominal width (NW) mm	7	10	12	15	20	27
L mm	41	41	45	45	50	61
L1 mm	28	28	32	32	37	48
PU units	10	10	10	10	10	10
Covering box units	180	180	160	150	120	80
<b>Item no.</b>	<b>09.0100</b>	<b>09.0101</b>	<b>09.0102</b>	<b>09.0103</b>	<b>09.0104</b>	<b>09.0106</b>



## GEKA® plus threaded fittings P with female thread

NBR flat seal ring on the threaded side


Female thread in mm	19.17	24.66	30.93	39.59	45.48
<b>Female thread</b>	<b>G1/2</b>	<b>G3/4</b>	<b>G1</b>	<b>G1 1/4</b>	<b>G1 1/2</b>
Nominal width (NW) mm	14	18	23	23	23
t mm	11	11	11	15	15
L mm	24	24	24	31	31
PU units	10	10	10	10	10
Covering box units	200	200	150	120	100
<b>Item no.</b>	<b>09.0110</b>	<b>09.0111</b>	<b>09.0113</b>	<b>09.0114</b>	<b>09.0116</b>



## GEKA® plus threaded fittings P with male thread

Conical sealing attachment at thread run-out

Male thread in mm	20.95	26.44	33.25	41.91
<b>Male thread</b>	<b>G1/2</b>	<b>G3/4</b>	<b>G1</b>	<b>G1 1/4</b>
Nominal width (NW) mm	14	19	23	23
t mm	11	13	13	15
L mm	24	24	26	28
PU units	10	10	10	10
Covering box units	200	180	180	140
<b>Item no.</b>	<b>09.0120</b>	<b>09.0121</b>	<b>09.0123</b>	<b>09.0124</b>



## GEKA® plus dummy coupling P

With bore for chain fastening

L mm	26
L1 mm	13
PU units	10
Covering box units	200
<b>Item no.</b>	<b>09.0118</b>

