

STORZ couplings *cast aluminium*

Advantage / benefit:..... cast version, suitable for low-duty applications and low pressures
Material:..... aluminium
Seal:..... NBR white
Operating pressure:..... max. 6 bar



STORZ suction couplings

Hose ID mm	32	38	52	65	75	100
Hose size	1¼"	1½"	2"	2½"	3"	4"
Lug spacing mm	66	66	66	89	89	133
STORZ size	52-C	52-C	52-C	75-B	75-B	110-A
PU units	1	1	1	1	1	1
Item no.	69.1004	69.1005	69.1007	69.1008	69.1009	69.1010



STORZ fixed couplings with female thread

Female thread in mm	39.59	45.48	57.29	72.86	85.56	110.71
Female thread	G1¼	G1½	G2	G2½	G3	G4
Lug spacing mm	66	66	66	89	89	133
STORZ size	52-C	52-C	52-C	75-B	75-B	110-A
PU units	1	1	1	1	1	1
Item no.	69.1022	69.1023	69.1025	69.1027	69.1028	69.1029



STORZ fixed couplings with male thread

Male thread in mm	41.91	47.80	59.61	75.18	87.88	113.03
Male thread	G1¼	G1½	G2	G2½	G3	G4
Lug spacing mm	66	66	66	89	89	133
STORZ size	52-C	52-C	52-C	75-B	75-B	110-A
PU units	1	1	1	1	1	1
Item no.	69.1036	69.1037	69.1038	69.1040	69.1041	69.1042

STORZ transition pieces

STORZ size 1	75-B	110-A
STORZ size 2	52-C	75-B
PU units	1	1
Item no.	69.1058	69.1059



STORZ blind couplings with chain

Lug spacing mm	66	89	133
STORZ size	52-C	75-B	110-A
PU units	1	1	1
Item no.	69.1052	69.1053	69.1054

