

# GEKA® plus watering wands Vario *metal*

- Advantage / benefit: ..... **quantity control valve (ball valve) with rotatable and pull-out telescopic outlet pipe and watering head for large-scale, soft water spray**
- Material: ..... GEKA® plus quick coupling: brass; ball valve (50.5548): brass nickel-plated; ball: hard chrome-plated; moulded handles, clamping nut and threaded sleeve: plastic PVC/PA; moulded seal ring: PP/EPDM fully cross-linked; watering head: aluminium; threaded insert: brass; telescopic outlet pipe: aluminium
- Connection: ..... GEKA® plus quick coupling suitable for hose sizes from 3/8" to 1 1/2"
- Options: ..... **telescopic outlet pipe either 80 cm long (can be extended to approx. 140 cm, pipe bend 35°) or 145 cm long (can be extended to approx. 225/400 cm, pipe bend 35°/135°) large selection of watering heads, showers and nozzles on the following pages**
- Area of application: ..... **highly recommended for watering inaccessible wall, balcony, hanging, terrestrial, roadside and hillside vegetation**



## GEKA® plus watering wands Vario

Water flow rate at 3 bar l/min	approx. 66	approx. 66
Sieve hole Ø mm	0.7	0.7
Pipe Ø in mm	20 x 1.25	20 x 1.25
Pipe bend	35°	35°
Pipe length in cm	80-140	145-225
PU units	1	1
Covering box units	30	20
<b>Item no.</b>	<b>48.0480.9</b>	<b>48.4150.9</b>

Water flow rate at 3 bar l/min	approx. 66	approx. 66
Sieve hole Ø mm	0.7	0.7
Pipe Ø in mm	20 x 1.25	20 x 1.25
Pipe bend	135°	135°
Pipe length in cm	145-225	240-400
PU units	1	1
Covering box units	20	20
<b>Item no.</b>	<b>48.5150.9</b>	<b>48.5151.9</b>